

## IVIOS LED III

### LED downlights



#### Product benefits

- Pleasant homogenous light
- Long lifetime thanks to LED technology
- Low installation depth

#### Product features

- Recessed LED downlight
- Type of protection: IP44
- Solid aluminum housing in white
- Beam angle: 90°
- Color temperature: 3,000 K
- Lifetime: up to 25,000 h
- Protection class: II
- Dimmable (with suitable Phase-cut dimmers)



# Product family datasheet

## Technical data

Product description	Electrical data			Photometrical data			Light technical data	Dimensions & weight			
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Color rendering index Ra	Beam angle	Length	Diameter	Height	Width
IVIOS LED III 10 W WT	10.0 W	220...240 V	50/60 Hz	3000 K	600 lm	≥ 80	90 °	110.0 mm	110.0 mm	43.0 mm	
IVIOS LED III 2X5.5 W WT	5 W	220...240 V	50/60 Hz	3000 K	330 lm	≥ 80	90 °	80.0 mm	80.0 mm	35.0 mm	80.0 mm

  

Product description	Colors & materials			Capabilities			Certificates & standards	
	Body material	Product color	Cover material	Type of installation	Adjustable	Dimmable	Protection class	Type of protection
IVIOS LED III 10 W WT	Aluminum	White	Polycarbonate (PC)	Recessed	No	Yes	II	IP44
IVIOS LED III 2X5.5 W WT	Aluminum	White	Polycarbonate (PC)	Recessed	No	Yes	III	IP44

  

Product description	Country specific categorizations
	Order reference
IVIOS LED III 10 W WT	41192
IVIOS LED III 2X5.5 W WT	41191

## Product family datasheet

---

### Equipment / Accessories

- External control gear included (cabled on the secondary side)
- 

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.