

# PRODUCT FAMILY DATASHEET

## LEDVANCE DAMP PROOF LED SLIM VALUE

### LED damp-proof luminaires



---

#### AREAS OF APPLICATION

- Industrial and storage facilities
- Car parks and underpasses
- Garages
- Workshops, assembly lines

---

#### PRODUCT BENEFITS

- Uniform light and wide beam angle
- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- Very slim design
- Easy installation as mounting brackets can be positioned freely on the luminaire
- Easy access to electrical terminal thanks end caps with clip mechanism
- Tool-free electrical connection due to push button connector
- 5 years guarantee

---

#### PRODUCT FEATURES

- Luminaire efficacy: up to 110 lm/W
- Beam angle: 120°
- Type of protection: IP65




TECHNICAL DATA

Product description	Electrical data				Photometrical data				Light technical data	Dimensions & weight	
	Operating mode	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Length	Width
DAMP PROOF LED SLIM VALUE 1200 36 W 4000 K <sup>1)</sup>	Electronic control gear (ECG)	36.00 W	220...240 V	50/60 Hz	4000 K	4000 lm	Cool White	>80	120 °	1200 mm	35.0 mm
DAMP PROOF LED SLIM VALUE 1200 36 W 6500 K <sup>1)</sup>	Electronic control gear (ECG)	36.00 W	220...240 V	50/60 Hz	6500 K	4000 lm	Cool Daylight	>80	120 °	1200 mm	35.0 mm
DAMP PROOF LED SLIM VALUE 1500 50 W 4000 K <sup>1)</sup>	Electronic control gear (ECG)	50.00 W	220...240 V	50/60 Hz	4000 K	5500 lm	Cool White	>80	120 °	1500 mm	35.0 mm
DAMP PROOF LED SLIM VALUE 1500 50 W 6500 K <sup>1)</sup>	Electronic control gear (ECG)	50.00 W	220...240 V	50/60 Hz	6500 K	5500 lm	Cool Daylight	>80	120 °	1500 mm	35.0 mm

Product description	Height	Colors & materials		Temperatures & operating conditions	Capabilities		Certificates & standards		
		Body material	Product color	Ambient temperature range	Dimmable	Type of connection	Luminous efficacy of lamp in luminaire	Protection class	Type of protection
DAMP PROOF LED SLIM VALUE 1200 36 W 4000 K <sup>1)</sup>	48.0 mm	Polycarbonate (PC)	White	-20...40 °C	No	Fixed connection (terminal)	110 lm/W	II	IP65
DAMP PROOF LED SLIM VALUE 1200 36 W 6500 K <sup>1)</sup>	48.0 mm	Polycarbonate (PC)	White	-20...40 °C	No	Fixed connection (terminal)	110 lm/W	II	IP65
DAMP PROOF LED SLIM VALUE 1500 50 W 4000 K <sup>1)</sup>	48.0 mm	Polycarbonate (PC)	White	-20...40 °C	No	Fixed connection (terminal)	110 lm/W	II	IP65
DAMP PROOF LED SLIM VALUE 1500 50 W 6500 K <sup>1)</sup>	48.0 mm	Polycarbonate (PC)	White	-20...40 °C	No	Fixed connection (terminal)	110 lm/W	II	IP65

<sup>1)</sup> Available from December 2017



DAMP PROOF LED SLIM VALUE 1200  
36 W 4000 K, DAMP PROOF LED SLIM  
VALUE 1200 36 W 6500 K

DAMP PROOF LED SLIM VALUE 1500  
50 W 4000 K, DAMP PROOF LED SLIM  
VALUE 1500 50 W 6500 K

### EQUIPMENT / ACCESSORIES

- Stainless steel clamps with safety screws included
- Mounting accessories included (suspension kit, theft protection kit)

### APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

### LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075066458	DAMP PROOF LED SLIM VALUE 1200 36 W 4000 K	Shipping carton box 20	1271 mm x 215 mm x 226 mm	61.76 dm <sup>3</sup>	14090.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075066472	DAMP PROOF LED SLIM VALUE 1200 36 W 6500 K	Shipping carton box 20	1271 mm x 215 mm x 226 mm	61.76 dm <sup>3</sup>	14090.00 g
4058075066496	DAMP PROOF LED SLIM VALUE 1500 50 W 4000 K	Shipping carton box 20	1571 mm x 215 mm x 226 mm	76.33 dm <sup>3</sup>	12832.00 g
4058075066519	DAMP PROOF LED SLIM VALUE 1500 50 W 6500 K	Shipping carton box 20	1571 mm x 215 mm x 226 mm	76.33 dm <sup>3</sup>	16890.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### REFERENCES / LINKS

For Guarantee see

▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.