

PRODUCT FAMILY DATASHEET

LEDVANCE OUTDOOR LED FACADE INDIRECT

Luminaires with rotatable head and indirect light



AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Homogeneous light output

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Available in two housing colors: white and dark gray
- Swivel angle: 90°
- Diffuser made of opal PMMA



TECHNICAL DATA

Product description	Electrical data						Photometrical data				
	Nominal wattage	Nominal voltage	Nominal current	Operating mode	Mains frequency	Power factor λ	Luminous efficacy	Luminous flux	Color temperature	Light color (designation)	Color rendering index Ra
LED FACADE INDIRECT 13 W 3000 K RD GY ¹⁾	13.00 W	220...240 V	0.063 A	Mains voltage	50/60 Hz	>0.5	35 lm/W	480 lm	3000 K	Warm White	≥80
LED FACADE INDIRECT 13 W 3000 K RD WT ¹⁾	13.00 W	220...240 V	0.063 A	Mains voltage	50/60 Hz	>0.5	50 lm/W	640 lm	3000 K	Warm White	≥80

Product description	Standard deviation of color matching	Light technical data	Dimensions & weight		Colors & materials	Temperatures & operating conditions	Lifespan		Additional product data
		Beam angle	Diameter	Height	Product color	Ambient temperature range	Number of switching cycles	Lifespan L70 at 25 °C	
LED FACADE INDIRECT 13 W 3000 K RD GY ¹⁾	<6 sdcM	240 °	150.0 mm	118.0 mm	Gray	-20...40 °C	15000	30000 h	Wall
LED FACADE INDIRECT 13 W 3000 K RD WT ¹⁾	<6 sdcM	240 °	150.0 mm	118.0 mm	White	-20...40 °C	15000	30000 h	Wall

Product description	Capabilities			Certificates & standards			
	Dimmable	LED module replaceable	Type of connection	Type of protection	Protection class	Protection class IK (shock resistance)	Photobiological safety group
LED FACADE INDIRECT 13 W 3000 K RD GY ¹⁾	No	Not replaceable	Terminal, 3-Pole (L, N, PE)	IP54	I	IK06	RG 0
LED FACADE INDIRECT 13 W 3000 K RD WT ¹⁾	No	Not replaceable	Terminal, 3-Pole (L, N, PE)	IP54	I	IK06	RG 0

Product description	Standards
LED FACADE INDIRECT 13 W 3000 K RD GY ¹⁾	CE
LED FACADE INDIRECT 13 W 3000 K RD WT ¹⁾	CE

1) Available from February 2018



LED FACADE INDIRECT 13 W 3000 K RD
GY, LED FACADE INDIRECT 13 W 3000 K
RD WT

EQUIPMENT / ACCESSORIES

– Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075016	LED FACADE INDIRECT 13 W 3000 K RD GY	Shipping carton box 6	300 mm x 275 mm x 185 mm	15.26 dm ³	5308.00 g

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075030	LED FACADE INDIRECT 13 W 3000 K RD WT	Shipping carton box 6	300 mm x 275 mm x 185 mm	15.26 dm ³	5308.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.