

Light is OSRAM

OSRAM

Our Brand

e:cue

SYMPL pro Node (e:pix)

e:cue Interfaces

Lighting applications are heterogenous by nature. e:cue interfaces serve to integrate many networks, protocols and third party products into e:cue solutions. They also aid in applying special control functions for fixtures, they integrate analog or mechanical signaling into the digital world and offer bridging functions. e:cue interfaces are the links to bring together the many techniques and technologies of lighting control.



e:cue SYMPL pro Node

The SYMPL pro Node is an eight-channel DMX / e:pix and RDM interface for use with e:cue's lighting control solution SYMPHOLIGHT. It provides eight independent DMX/RDM interfaces for eight DMX512 universes with 4096 channels. Also available as e:pix version (16384 channels). The SYMPL pro Node is especially designed for projects in tough outdoor environments. Connection to the server runs via Ethernet interface with 100 Mbit/s. The SYMPL pro Node can be powered by an external power supply or via Power-over-Ethernet. It is easily mounted on standard 35 mm DIN rails, or with a key hole in the housing base on walls or on any stable vertical surface. The SYMPL pro Node is a simple, reliable and easy to use interface solution for e:cue lighting control solutions with SYMPHOLIGHT.

Highlights

- 8 independent interfaces for DMX512/RDM or e:pix/RDM
- Flexible mounting on 35 mm DIN rails or vertical surfaces
- Simple and easy integration in e:cue SYMPHOLIGHT
- Extended operating temperature -40 ... 70°C
- Embedded temperature & humidity sensors
- Backup-mode on data loss
- Integrated protection against surge
- Reverse polarity protection
- Power-over-Ethernet
- Test mode via button
- Web interface for status and configuration

Delivery scope

- e:cue SYMPL pro Node DMX with CE only
- e:cue SYMPL pro Node e:pix
- Safety instructions
- Installation guide English

Identcode

AM255360031
AM305660031
AM305690031

Optional accessories

- Power supply 15W 24V DIN rail

AM1884100HA

Technical data

Dimensions (W x H x D)	143 x 92 x 62 mm/5.63 x 3.6 x 2.4 in (excl. fastening clip)
Weight	250 g / 0.55 lb
Power supply	24 ... 48 V DC (terminal plug) wire gauge: 0,21 ... 3,31 mm ² ; or PoE IEEE 802.3af on RJ45
Power consumption	max. 8 W (incl. DMX termination)
Operating temperature	-40 ... 70 °C * / -4 ... 158 °F *
Storage temperature	-40 ... 70 °C / -4 ... 158 °F
Electrical safety	SELV
Operating/storage hum.	0 ... 80% non-condensing
Protection Class	IP20
Housing material	Self extinguishing blend PC/ABS
Mounting	on 35 mm DIN rail (DIN 43880) (19-inch rack), or with key hole on any stable vertical surface
Certification	CE, ETL
Interfaces	8 x DMX512/RDM, or 8 x e:pix/RDM isolated in pairs (3.75 kV), surge protection, reverse polarity protection, 3-pin terminal plug wire gauge: 0.08 ... 1.31 mm ²
Interface specifications	$V_{DMXmax}/V_{DMXmin} = 4.6 V/0.8 V$ Short circuit protected: $I_{SCmax} = 100 mA$
Ethernet-Port	1 x e:net 10/100 Mbit/s RJ-45, surge protection
Sensors	Temperature -40 ... 120 ±°C (0.2 °C) Humidity 0 ... 100% (±2%)
User interface	LEDs for error, Ethernet activity, device status, DMX/RDM status Identify button, Test button

* 70 °C / 158 °F for max. 1 hour/day; continuous operation at max. 60 °C / 140 °F.



Conforms to UL Std. 62368-1
Certified to CSA Std. C22.2 NO. 62368-1

This document contains proprietary information of e:cue and is tendered subject to the conditions that the information be retained in confidence not be reproduced or copied and not be used or incorporated in any product.

Subject to modification without prior notice. Typographical and other errors do not justify any claim for damages. All dimensions should be verified using an actual part.

OSRAM GmbH
Karl-Schurz-Strasse 38
33100 Paderborn, Germany
www.traxontechnologies.com
www.ecue.com

Sheet: 1/2
Rev. 20200420

Light is OSRAM

OSRAM

Our Brand

ecue

SYMPL pro Node (e:pix)

Dimensions

All measures in mm

