

---

## NOXLITE LED WALL

### Outdoor LED wall luminaires



---

#### Areas of application

- Outdoor
- Patios, balconies

---

#### Product benefits

- Elegant design
- Quick and simple installation
- High-power LED for high light output
- Compact and lightweight

---

#### Product features

- Intelligent and elegant outdoor LED luminaire
- Motion and day/night sensor with time settings from 5 s...10 min
- Type of protection: IP44



# Product family datasheet

## Technical data

Product description	Electrical data				Photometrical data				Light technical data	Dimensions & weight
	Nominal wattage	Nominal voltage	Mains frequency	Operating mode	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Length
NOXLITE LED WALL 6 W SINGLE SENSOR GR	6 W	100...240 V	50...60 Hz	ECG	6000 K	210 lm	Cool white	> 65	122 °	229.0 mm
NOXLITE LED WALL 6 W SINGLE SENSOR SI	6 W	100...240 V	50...60 Hz	ECG	6000 K	210 lm	Cool white	> 65	122 °	229.0 mm
NOXLITE LED WALL 12 W DOUBLE SENSOR GR	12.0 W	100...240 V	50...60 Hz	ECG	6000 K	460 lm	Cool white	> 65	135 °	123.0 mm
NOXLITE LED WALL 12 W ROUND SENSOR GR	12.0 W	100...240 V	50...60 Hz	ECG	6000 K	400 lm	Cool white	> 65	168 °	172.0 mm
NOXLITE LED WALL 12 W DOUBLE SENSOR SI	12.0 W	100...240 V	50...60 Hz	ECG	6000 K	460 lm	Cool white	> 65	135 °	123.0 mm
NOXLITE LED WALL 12 W ROUND SENSOR WT	12.0 W	100...240 V	50...60 Hz	ECG	6000 K	400 lm	Cool white	> 65	168 °	172.0 mm
NOXLITE LED WALL 12 W ROUND	12.0 W	100...240 V	50...60 Hz	ECG	3000 K	310 lm	Cool white		168 °	172.0 mm

Product description	Width	Height	Colors & materials			Temperatures	Lifespan	Additional product data	
			Body material	Product color	Cover material	Ambient temperature range	Lifespan	Number of lighting outlets	Equipment
NOXLITE LED WALL 6 W SINGLE SENSOR GR	123.0 mm	82.0 mm	Aluminum	Grey	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h	3	LED
NOXLITE LED WALL 6 W SINGLE SENSOR SI	123.0 mm	82.0 mm	Aluminum	Silver	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h	3	LED

## Product family datasheet

Product description	Width	Height	Colors & materials			Temperatures	Lifespan	Additional product data	
			Body material	Product color	Cover material	Ambient temperature range	Lifespan	Number of lighting outlets	Equipment
NOXLITE LED WALL 12 W DOUBLE SENSOR GR	270.0 mm	82.0 mm	Aluminum	Grey	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h		LED
NOXLITE LED WALL 12 W ROUND SENSOR GR	172.0 mm	82.0 mm	Aluminum	Grey	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h	6	LED
NOXLITE LED WALL 12 W DOUBLE SENSOR SI	270.0 mm	82.0 mm	Aluminum	Silver	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h	6	LED
NOXLITE LED WALL 12 W ROUND SENSOR WT	172.0 mm	82.0 mm	Aluminum	White	Polymethyl methacrylate (PMMA)	-20...+40 °C	30000 h	6	LED
NOXLITE LED WALL 12 W ROUND	172.0 mm	72.0 mm	Aluminum	Grey	Polymethyl methacrylate (PMMA)		30000 h	6	LED

Product description	Equipped with lamp	Capabilities				
		Type of installation	Adjustable	Dimmable	Type of connection	Accessories
NOXLITE LED WALL 6 W SINGLE SENSOR GR	Yes	Surface-mounted	Yes	No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor cap / Sensor limitation strip
NOXLITE LED WALL 6 W SINGLE SENSOR SI	Yes	Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor limitation strip
NOXLITE LED WALL 12 W DOUBLE SENSOR GR	Yes	Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor limitation strip
NOXLITE LED WALL 12 W ROUND SENSOR GR	Yes	Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor limitation strip
NOXLITE LED WALL 12 W DOUBLE SENSOR SI	Yes	Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor limitation strip
NOXLITE LED WALL 12 W ROUND SENSOR WT	Yes	Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	Screw / Sensor limitation strip

## Product family datasheet

Product description	Equipped with lamp	Capabilities				Accessories
		Type of installation	Adjustable	Dimmable	Type of connection	
NOXLITE LED WALL 12 W ROUND		Surface-mounted		No	Terminal, 3-pole, max. 1,5 mm <sup>2</sup>	

Product description	Certificates & standards			Type of protection	Country specific categorizations
	Standards	Protection class	Order reference		
NOXLITE LED WALL 6 W SINGLE SENSOR GR	CE	II		IP44	41016
NOXLITE LED WALL 6 W SINGLE SENSOR SI	CE	II		IP44	41039
NOXLITE LED WALL 12 W DOUBLE SENSOR GR	CE	II		IP44	41017
NOXLITE LED WALL 12 W ROUND SENSOR GR	CE	II		IP44	41018
NOXLITE LED WALL 12 W DOUBLE SENSOR SI	CE	II		IP44	41040
NOXLITE LED WALL 12 W ROUND SENSOR WT	CE	II		IP44	41041
NOXLITE LED WALL 12 W ROUND		II		IP44	41019

## Product family datasheet

---

### Application advice

For more detailed application information and graphics please see product datasheet.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.