
PUNCTOLED II

LED downlights



Product family datasheet

Technical data

Product description	Electrical data			Photometrical data				Light technical data	Dimensions & weight		Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter	Height	Body material
PUNCTOLED II 10 W	10.0 W	220...240 V	50/60 Hz	3000 K	600 lm	Warm white	≥ 80	90 °	85.0 mm	54.0 mm	Aluminum
PUNCTOLED II 15 W	15.0 W	220...240 V	50/60 Hz	3000 K	1000 lm	Warm white	≥ 80	90 °	110.0 mm	73.0 mm	Aluminum
PUNCTOLED II 20 W	20.0 W	220...240 V	50/60 Hz	3000 K	1450 lm	Warm white	≥ 80	90 °	135.0 mm	76.0 mm	Aluminum

Product description	Product color	Cover material	Capabilities				Type of connection	Certificates & standards
			Type of installation	Adjustable	Dimmable	Protection class		
PUNCTOLED II 10 W	White	Aluminum	Recessed	No	Yes	Fixed (cutting terminal)	II	
PUNCTOLED II 15 W	White	Aluminum	Recessed	No	Yes	Fixed (cutting terminal)	II	
PUNCTOLED II 20 W	White	Aluminum	Recessed	No	Yes	Fixed (cutting terminal)	II	

Product description	Type of protection	Country specific categorizations
		Order reference
PUNCTOLED II 10 W	IP20	41079
PUNCTOLED II 15 W	IP20	41080
PUNCTOLED II 20 W	IP20	41081

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.