

PRODUCT FAMILY DATASHEET

LEDVANCE OUTDOOR LED SURFACE POLE

Stainless steel surface-luminaires with indirect illumination



AREAS OF APPLICATION

- Outdoor
- Building facades
- Decorative illumination

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP44
- Housing made of Polycarbonate covered with stainless steel
- Available as wall, ceiling and bollard luminaires
- Diffuser made of transparent polycarbonate



TECHNICAL DATA


Product description	Electrical data						Photometrical data				
	Nominal wattage	Nominal voltage	Nominal current	Operating mode	Mains frequency	Power factor λ	Luminous efficacy	Luminous flux	Color temperature	Light color (designation)	Color rendering index Ra
LED SURFACE POLE 6 W 3000 K SST 1)	6.00 W	220...240 V	0.06 A	Mains voltage	50/60 Hz	>0.5	60 lm/W	360 lm	3000 K	Warm White	≥80

Product description	Standard deviation of color matching	Light technical data	Dimensions & weight		Colors & materials	Temperatures & operating conditions	Lifespan	Additional product data	
		Beam angle	Diameter	Height	Product color	Ambient temperature range	Number of switching cycles		Lifespan L70 at 25 °C
LED SURFACE POLE 6 W 3000 K SST 1)	<6 sdc	160 °	102.0 mm	87.0 mm	Steel	-20...40 °C	15000	30000 h	Ceiling / Wall

Product description	Capabilities			Certificates & standards			
	Dimmable	LED module replaceable	Type of connection	Type of protection	Protection class	Protection class IK (shock resistance)	Photobiological safety group
LED SURFACE POLE 6 W 3000 K SST 1)	No	Not replaceable	Terminal, 2-Pole (L, N)	IP44	II	IK06	RG 0

Product description	Standards
LED SURFACE POLE 6 W 3000 K SST 1)	CE

1) Available from February 2018



LED SURFACE POLE 6 W 3000 K SST

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075075177	LED SURFACE POLE 6 W 3000 K SST	Shipping carton box 6	380 mm x 175 mm x 320 mm	21.28 dm ³	2091.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- ▶ www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.