
PUNCTOLED I

LED downlights



Areas of application

- Corridors
- Wardrobes
- Downlights

Product benefits

- High brightness thanks to LED technology
- Simple installation
- High-value design
- Energy-saving alternative to luminaires that use halogen lamps

Product features

- Dimmable (with suitable dimmers)
- Adjustable head
- Color temperature: 3,000 K
- Solid aluminum housing in white
- High-power LED
- Type of protection: IP33



Product family datasheet

Technical data

Product description	Electrical data			Photometrical data				Light technical data	Dimensions & weight		Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Color temperature	Luminous flux	Light color (designation)	Color rendering index Ra	Beam angle	Diameter	Height	Body material
PUNCTOLED I 2x8.5 W	8.5 W	220...240 V	50/60 Hz	3000 K	450 lm	Warm white	≥ 80	25 °	85.0 mm	70.0 mm	Aluminum
PUNCTOLED I 2x4.5 W	4.5 W	220...240 V	50/60 Hz	3000 K	220 lm	Warm white	≥ 80	25 °	66.0 mm	42.0 mm	Aluminum
PUNCTOLED I 10.5 W	10.5 W	220...240 V	50/60 Hz	3000 K	625 lm	Warm white	≥ 80	25 °	98.0 mm	65.0 mm	Aluminum

Product description	Product color	Additional product data	Capabilities				Certificates & standards
		Equipment	Type of installation	Adjustable	Dimmable	Type of connection	Protection class
PUNCTOLED I 2x8.5 W	White	LED	Recessed	Yes	Yes	Connector	II
PUNCTOLED I 2x4.5 W	White	LED	Recessed	Yes	Yes	Connector	II
PUNCTOLED I 10.5 W	White	LED	Recessed	Yes	Yes	Fixed (cutting terminal)	II

Product description	Type of protection	Country specific categorizations
		Order reference
PUNCTOLED I 2x8.5 W	IP33	41077
PUNCTOLED I 2x4.5 W	IP33	41076
PUNCTOLED I 10.5 W	IP33	41078

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.