
NOXLITE SMART SPOT

Outdoor LED wall luminaires



Areas of application

- Driveways
- Garages
- Terraces
- Paths
- Gardens

Product benefits

- Smart grouping with master/slave arrangement
- Flexible direction of light thanks to movable luminaire heads
- Energy-efficient thanks to LED technology
- Easy installation with fast connection

Product features

- Type of protection: IP55
- Invisible integrated high-frequency and light sensor



Product family datasheet

Technical data

Product description	Electrical data				Photometrical data			Dimensions & weight		Colors & materials
	Nominal wattage	Nominal voltage	Mains frequency	Operating mode	Color temperature	Luminous flux	Light color (designation)	Width	Height	Body material
NOXLITE SMART SPOT SINGLE	7.5 W	230 V	50/60 Hz	ECG	3000 K	500 lm	Warm white	86.0 mm	200.0 mm	Aluminum
NOXLITE SMART SPOT DOUBLE	13.0 W	230 V	50/60 Hz	ECG	3000 K	1000 lm	Warm white	179.0 mm	200.0 mm	Aluminum

Product description	Product color	Cover material	Temperatures	Capabilities		Certificates & standards	Country specific categorizations
			Ambient temperature range	Type of installation	Type of connection	Type of protection	Order reference
NOXLITE SMART SPOT SINGLE	White	Plastic	-20...+40 °C	Direct mounting	Terminal, 3-pole	IP55	NOXLITE SMART S
NOXLITE SMART SPOT DOUBLE	White	Plastic	-20...+40 °C	Direct mounting	Terminal, 3-pole	IP55	NOXLITE SMART D

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.