

## **OPTOTRONIC OT 120/220-240/24 DIM P**

---

Power supplies for LED modules

- Outdoor applications

### **Product benefits**

---

- High surge protection: up to 3 kV (L-N) / 6 kV (L/N-PE)
- High IP protection (IP67)
- Slim housing design and flexible mounting concept

### **Product features**

---

- SELV equivalent
- Dimmable via fully insulated 1...10 V interface



---

*Product line drawing with letters*

## Technical data

Product description	Nominal current	Ambient temperature range	Input voltage	Nominal voltage	Mains frequency	Output voltage
	0.60 A <sup>1)</sup>	-25...+55 °C	198...264 V <sup>2)</sup>	220...240 V	50/60 Hz	24 V <sup>3)</sup>

Product description	Dimming interface	Dimming range	Maximum temperature at tc test point	Maximum wiring length ECG/lamp
	1...10 V	1...100 %	80 °C <sup>4)</sup>	10 m

<sup>1)</sup> At 230 V

<sup>2)</sup> Permitted voltage range

<sup>3)</sup> +1.0/-0.5 V

<sup>4)</sup> Maximum at the Tc-point

## **Application advice**

---

For more detailed application information and graphics please see product datasheet.

## **Disclaimer**

---

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.