

PRODUCT FAMILY DATASHEET LEDVANCE OUTDOOR LED FACADE LANTERN

Contemporary lanterns with light guide for low-glare illumination



AREAS OF APPLICATION

- Outdoor
- Building facades
- Gardens, balconies and other outdoor areas

PRODUCT BENEFITS

- Energy-efficient thanks to LED technology
- 5 years guarantee
- Easy and quick installation
- Special light guide design for low-glare illumination

PRODUCT FEATURES

- Bright and functional outdoor LED luminaires
- Type of protection: IP54
- Die-cast aluminum housing
- Diffuser made of opal polycarbonate with transparent polycarbonate cover



TECHNICAL DATA


	Electrical da	Electrical data						Photometrical data				
Product description	Nominal wattage	Nominal voltage	Nominal current	Operating mode	Mains frequency	Power factor λ	Luminous efficacy	Luminous flux	Color temper- ature	Light color (designation)	Color render- ing index Ra	
LED FACADE LANTERN 12 W 3000 K	12.00 W	220240 V	0.096 A	Mains voltage	50/60 Hz	>0.5	50 lm/W	610 lm	3000 K	Warm White	≥80	

		Light technical data	Dimensions & w	eight		Colors & materials	Temperatures & operating conditions	Lifespan	Additional product data
Product description	Standard deviation of color matching	Beam angle	Length	Width	Height	Product color	Ambient temperature range	Number of switching cycles	Mounting location
LED FACADE LANTERN 12 W 3000 K	<6 sdcm	210.00 °	176.0 mm	110.0 mm	240.0 mm	Gray	-2040 °C	15000	Wall

	Capabilities	Certificates & standards					
Product description	Dimmable	LED module replaceable	Type of connection	Type of protection	Protection class	Protection class IK (shock resistance)	Photobiological safety group
LED FACADE LANTERN 12 W 3000 K	No	Not replaceable	Terminal, 3-Pole (L, N, PE)	IP54	1	IK06	RG 0

Product description	Standards
LED FACADE LANTERN 12 W 3000 K	CE
GY ¹⁾	

¹⁾ Available from February 2018



LED FACADE LANTERN 12 W 3000 K GY

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

APPLICATION ADVICE

For more detailed application information and graphics please see product datasheet.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075074835	LED FACADE LANTERN 12 W 3000 K GY	Shipping carton box 4	425 mm x 285 mm x 315 mm	38.15 dm³	5822.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.