

# EASY RC | User interfaces for light management systems



## **Product features**

- 868.3 MHz radio receiver
- Connection via four-pole screw terminal or modular 4p4c-connector




### **Technical data**

### **Dimensions & weight**

Length	118.0 mm
Height	21.0 mm
Width	30.0 mm





Product line drawing with letters

#### Temperatures

Ambient temperature range	0+50 °C
, and the second s	

### Capabilities

Dimming interface	EASY	
Type of installation	Luminaire integration/Ceiling integration	
Transmitter range	30 m <sup>1)</sup>	

<sup>1)</sup> <sub>Maximum</sub>



### Certificates & standards

Type of protection

IP20



## **Equipment / Accessories**

 $\boldsymbol{\cdot}$  Suitable for up to 8 EASY Hybrid Remote units or 8 EASY Color Drive



## Logistical Data

Product code	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Gross weight	Volume
4008321421753	Folding carton box 1	69 mm x 24 mm x 140 mm	99.50 g	0.23 dm <sup>3</sup>
4008321421760	Shipping carton box 18	215 mm x 113 mm x 350 mm	2105.00 g	8.50 dm <sup>3</sup>



### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.