

EASY DMX 64x4 SO | Control units for light management systems



Product benefits

- Dimming, ON/OFF via conventional switches
- Configuration via the EASY Color Control software
- Test procedures for rapid error-free installation without software

Product features

- Individual control of up to 256 DMX channels
- Control of up to 64 independent light points
- Up to 64 lighting scenes and 4 sequences can be programmed




Technical data

Electrical data

| System wattage | 2.5 W |
|-----------------|----------|
| Nominal voltage | 100240 V |
| Mains frequency | 50/60 Hz |

Dimensions & weight

| Length | 108.0 mm |
|--------|----------|
| Height | 61.0 mm |
| Width | 96.0 mm |



Product line drawing with numbers

Temperatures

| Ambient temperature range | 0+50 °C |
|---------------------------|---------|

Product datasheet



Capabilities

| Dimming interface | DMX / EASY | |
|---------------------------|-------------------|--|
| Type of installation | DIN rail mounting | |
| Number of control outputs | 1 | |

Certificates & standards



Equipment / Accessories

- ${\boldsymbol{\cdot}}$ Suitable for simple control of luminaires and devices via DMX addresses
- DALI Plug&Play expansion via DALI EASY SO



Logistical Data

| Product code | Packaging unit (Pieces/Unit) | Dimensions (height x width x length) | Gross weight | Volume |
|---------------|---------------------------------|--------------------------------------|--------------|-----------|
| 4008321441560 | Folding carton box 1 | 155 mm x 73 mm x 224 mm | 326.00 g | 2.53 dm³ |
| 4008321441577 | Shipping carton box 6 | 243 mm x 243 mm x 325 mm | 2227.00 g | 19.19 dm³ |

Product datasheet



Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.